
L20/480 SLIDING HYGIENIC GRP DOORSETS

Dortek F Type Fire Rated Single Sliding Door Sets

- Manufacturer : Dortek Ltd St Mark Street Hull HU8 7ED United Kingdom Tel +44 (0)1482 226848
Fax +44 (0) 1482 226843 e-mail info@dortek.com
- Door : The doors shall be seamless glass-fibre reinforced polyester moulded around non-organic hi-density closed cell core. Doors wider than 1125mm will have a hygienic gel coat vertical joint.
- Reference : Dortek Type F30 *or* F60 *or* F90 Single – HS-SL single leaf sliding door
- Sizes : *See list of manufacturers standard sizes*
- Core : Vermiculite board 35mm thick and of 380kg per cubic metre density thermal conductivity 0.05 W/m sq
- Facing : Seamless hygienic moulded fire retardant polyester, 2.5mm thick. moisture absorption zero.
- Door leaf : 40mm thick.
- Finish : Smooth non-porous fire retardant gelcoat finish with built in colour
- Colour : Standard white *or* choice of 20 colours see chart *or* RAL / BS to order.
- Door frame : GRP with smoke seal and intumescent in PVC holder.
- Fire Rating : As building regulations and fire officer requirements tested to BS 476 part 22
- Ironmongery : Stainless steel flush & pull handles. *Specify. Locks etc*
- Track : Aluminium rail system with nylon bearings
- Guide : Internal bottom track with nylon guide
- Glazing : Triple glazed with laminate safety glass outer panes finished flush with both faces of door, centre pane Georgian wired *or* ceramic glass, (30 & 60 min doors only)
Size 200 x 300mm *or* 200 x 600mm *or* 300 x 600mm *or* 400 x 600mm positioned 165mm from leading edge *or other sizes on request*
- Canopy : Polyester powder coated *or* Stainless steel with sloping top.
- Operation : Electrical automation microprocessor controlled with safety photo-cell, in-built safety sensor to open the door if obstructed operated with 2 push buttons *or* 2 touchless sensors *or* 2 infra red detectors.
Specify Battery back-up to operate door in case of power failure