

## L20/480 HINGED HYGIENIC GRP DOORSETS

### **Dortek F Type Fire Rated Double Action Hinged Door Sets**

- Manufacturer : Dortek Limited, St Marks St., Hull HU8 7ED, United Kingdom  
Tel: +44 (0) 1482 226 848 Fax + 44 (0) 1482 226 843 email info@dortek.com
- Door: : The doors shall be of seamless glass fibre reinforced polyester moulded around non-organic hi-density core.
- Reference : Dortek Type F30- or F60- or F120- or F240 - Single double action or Pair double action
- Sizes : *See list of manufacturers standard sizes.*
- Core : Vermiculite board, 35mm thick and of 380kg per cubic metre density.  
Thermal conductivity 0.05 W/m sq.
- Facing : Seamless hygienic moulded fire retardant polyester 2.5mm thick. Moisture absorption zero.
- Door leaf: 40mm thick.
- Finish : Smooth non-porous fire retardant gel-coat finish with built in colour.
- Colour : Standard White *or choice of 20 colours see chart or RAL / BS to order*
- Door frame : GRP with smoke seal and intumescent in PVC holder.
- Fire Rating : As building regulations and fire officer requirement tested to BS 476 part 22
- Ironmongery : Geze double action floor spring with top pivot built into GRP frame  
*specify locks etc*
- Glazing : Triple glazed with laminate safety glass outer panes finished flush with both faces of door, centre pane Georgian wired or ceramic glass, (30 & 60 min doors only)  
Size 200 x 300mm or 200 x 600mm or 300 x 600mm or 400 x 600  
positioned 165mm from leading edge *or other sizes on request*
- Protection : 3mm thick ribbed rubber standard colour grey, or 2mm thick smooth finish high impact grey PVC or 0.7mm thick stainless steel, bonded to door leaf
- Fixing : Fix direct to structure with stainless steel screws.