

DT 7 Orion Freezer Door

Ideal for use in conditioned areas such as commercial coolers and kitchens. Due to the hygienic finish the DT7 Orion Freezer is suitable for preserving a food safe environment.

- Sliding movement
- System is airtight
- Resistant to extremely low temperatures

Optional extras;

- Automation
- Lock
- Stainless steel canopy

Thermal transmittance (Ud)

1000 x 2100mm = 0.418 W/m².K

3000 x 3000mm = 0.274 W/m²

DT7 sliding freezer door -40° C

Size range (Inside frame measurement)

- Single 1000-1600mm x 2100-2400mm WxH
- Manufactured in 100mm increments were applicable

Door blade

- 170mm thick high density injected polyurethane core

Finishes

- Food safe polyester coated White (RAL9010) or stainless steel.

Gaskets

- Tough rubber tubular gasket for perfect sealing

Handles

- Cam lever handle with euronorm lock/emergency release

Frames

- 45mm x 150mm polyester coated white (RAL9010) steel
- 240 V frame heating

Rail

- Patented aluminium rail system with indentations and nylon bearings

Canopy

- Sloping, removeable, polyester coated white (RAL9010) steel



Dortek Limited, Ireland
North Quay, Wicklow Town
County Wicklow, A67 HE26
Ireland
Tel: +353 (0) 404 67101
Fax: +353 (0) 404 67012
Email: ireland@dortek.com

Dortek Limited, UK
St Mark Street
Hull, HU8 7ED
England
Tel: +44 (0) 1482 226848
Fax: +44 (0) 1482 226843
Email: info@dortek.com

Dortek Inc
One Boston Place
Suite 2600
Boston
MA 02108
Tel: +1 617 401 8226
Email: us-sales@dortek.com

Dortek, Singapore
Dortek Hygienic Door
Systems Pte Ltd 627A
Ajunied Road
BizTech Centre 04-06
Singapore
389842 Tel: +65 67411787
Email: info@dortek.com

Dortek, Malaysia
Dortek Sdn Bhd
No 5 Jalan Desa Tropika 1/3
Taman Perindustrian Tropika
81800 Ulu Tiram
Johor
Malaysia
Tel: +60 7861 6233
Email: info@dortek.com

Dortek, New Zealand
2C, 40 Charlotte Street
Eden Terrace
Auckland 1022
New Zealand
Tel: +64 220722091
Email: info@dortek.com



DT 7 Polaris Chiller Door

Ideal for use in conditioned areas such as cold storage and distribution centres. The DT7 Polaris Chiller is robust and has a hygienic finish, specially designed for industrial environments with a large number of production moves.

- Sliding movement
- System is airtight
- Can be used in wet areas

Optional extras;

- Automation
- Stainless steel canopy

Thermal transmittance (Ud)

1000 x 2100mm = 0.514 W/m².K

3000 x 3000mm = 0.397 W/m².K

DT7 sliding chiller door 0° to +60° C

Size range (Inside frame measurement)

- Single 1000-3500mm x 2100-4000mm WxH
- Manufactured in 100mm increments were applicable

Door blade

- 80mm thick high density injected polyurethane core
- Protective bumper

Finishes

- Food safe polyester coated White (RAL9010), Grey/white (RAL9002) or stainless steel

Gaskets

- Tough rubber tubular gasket for perfect sealing

Handles

- Cam lever handle with euronorm lock/emergency release

Frames

- 45mm x 150mm polyester coated White (RAL9010), Grey/white (RAL9002) steel
- 240 V frame heating

Rail

- Patented aluminium rail system with indentations and nylon bearings

Canopy

- Sloping, removeable polyester coated White (RAL9010), Grey/white (RAL9002) steel



Dortek Limited, Ireland
North Quay, Wicklow Town
County Wicklow, A67 HE26
Ireland
Tel: +353 (0) 404 67101
Fax: +353 (0) 404 67012
Email: ireland@dortek.com

Dortek Limited, UK
St Mark Street
Hull, HU8 7ED
England
Tel: +44 (0) 1482 226848
Fax: +44 (0) 1482 226843
Email: info@dortek.com

Dortek Inc
One Boston Place
Suite 2600
Boston
MA 02108
Tel: +1 617 401 8226
Email: us-sales@dortek.com

Dortek, Singapore
Dortek Hygienic Door
Systems Pte Ltd 627A
Aljunied Road
BizTech Centre 04-06
Singapore
389842 Tel: +65 67411787
Email: info@dortek.com

Dortek, Malaysia
Dortek Sdn Bhd
No 5 Jalan Desa Tropika 1/3
Taman Perindustrian Tropika
81800 Ulu Tiram
Johor
Malaysia
Tel: +60 7861 6233
Email: info@dortek.com

Dortek, New Zealand
2C, 40 Charlotte Street
Eden Terrace
Auckland 1022
New Zealand
Tel: +64 220722091
Email: info@dortek.com

